

E-Z Arm[®] 2.5 Extractor Arm



Options

• Filtration Units:

HEPA, cartridge, and odor-control filter systems available based on application.

• Blower Packages:

Multiple options available to meet application-specific criteria.

Diversified Air Systems, Inc.

Phone: 800-264-8958

Email: info@divers-air.com

www.divers-air.com

Features & Benefits

• 2.5-in. dia. arm in 4- or 6-foot lengths

Provides for high-efficiency source-point collection for close work areas.

• 4.75-in. dia. flanged intake hood:

Increases collection area and efficiency.

• Strong, extruded aluminum tubing:

Epoxy powder coated for for corrosion resistance; lightweight for one-hand positioning.

• Triple-joint section design:

Provides complete 360° range of movement, allows for positive positioning in any setup.

• Heavy-duty stamped aluminum joints:

External friction adjustments can handled contunued repositioning with losing position integrity.

• Universal wall/table mounting bracket:

Allows multiple mounting options to maximize operator productivity and space usage.

• Flange-up or flange-down design:

Allows table or wall mounting configuration.

Specifications

Construction:

18 ga. extruded aluminum seamless tube with spiral flex duct

Arm Lengths:

4 ft. (E-Z Arm® 2.5 2EO4), 6 ft. (E-Z Arm® 2.5 2EO6)

Blower Pkgs (HP):

consult factory

Nominal CFM (in.):

75 to 300

Weight (lbs.):

E-Z Arm® 2.5 2EO4 - 5 lbs., 2EO6 - 6 lbs.

