



Portable Paint Booth

Features & Benefits

- **Portable, self-contained unit:**
Easy to set up and use anywhere; includes casters for added maneuverability.
- **Heavy-duty top mounted table with 300 PSF rated steel grate:**
Provides maximum loading of up to 550 lbs.
- **High efficiency 2-stage filtration:**
Provides up to 95% filtration efficiency.
- **Direct-drive blower:**
Higher static pressure, longer filter life and greater reliability; non-sparking; no belts or pulleys to replace.
- **Ultra-Seal® filter mounting:**
Eliminates contaminant bypass of filters.
- **Removable doors:**
Easy access for cleaning and filter changeout.
- **Prewired to explosion proof box:**
Meets Group-D electrical requirements.

Dimensions

Width:	32.00"
Height:	76.00"
Depth:	25.00"

Options

- **Pressure Gauge Kit:**
Indicates when filters require cleaning.
- **95% Main Filter and Double Adsorption Modules**
- **Motor Starters/Disconnects**
- **Plastic Coated Grate**
- **Aluminum Grate**

Specifications

Construction:

16 ga. steel, powder coated cabinet

Blower Pkgs (HP):

1.5

Noise Level (dBA):

72

Electrical: Group-D

1.5 HP - 115/208-230/1/60, 17.0/8.5 amps, std.
208-230/460/3/60/50, 4.9-4.6/2.3 amps, opt.

Nominal CFM (in.):

800

Weight (lbs.):

250

Diversified Air Systems, Inc.
Phone: 800-264-8958
Email: info@divers-air.com
www.divers-air.com

SPECIFICATIONS:

CONSTRUCTION:

16 Gauge steel cabinet finished with a Powder-Coat finish, includes locking filter mounting system, removable access doors to filters and direct drive motor and spark-resistant blower, top mounted grinding table with a heavy duty 300 PSF rated steel grate (max. table loading 550 lbs.), heavy duty 5" casters, power cord, and on-off switch, 3 phase motors wired to junction box outside of unit. Meets electrical requirements for Class 1, Group-D. (Motor starters/disconnects not included. Option only.)

FILTER SEAL:

Positive sealing filter locking mechanism for all main filters. Requires no tools. Ultra-Seal™ on bag, main filter and AD.

PREFILTERS:

- (1) 2" Aluminum mesh, std.
- (1) 2" Polyester, opt.

MAIN FILTERS:

- 95% Main filter and AD Module (18 lbs.), std.
- 95% Main filter and double AD's (36 lbs.), opt.

OTHER OPTIONS:

- Pressure gauge kit indicates filter changes
- Plastic coated grate.
- Aluminum grate

FIRE SUPPRESSION: Equipment provided by others.

* AFS FILTER EFFICIENCIES BASED ON ASHRAE 52-76 TEST METHOD



WEIGHT: 250 lbs.

DOWNDRAFT VELOCITY: 150 FPM with std. 1.5 HP motor

NOISE: 72 dBA

ELECTRICAL:

- 1.5 HP 115/208-230/1/60, 17.0/8.5 amps, std. Hazard location Group-D
- 1.5 HP 208-230/460/3/60/50, 4.9-4.6/2.3 amps, opt. Hazard location Group-D



NOTES:

Items designated as are included in this proposal.

THE DEVICE DEPICTED AND DESCRIBED HEREON EMBODIES PROPRIETARY INFORMATION OWNED BY AIRFLOW SYSTEMS, INC. ALL DESIGN, MANUFACTURING, REPRODUCTION, SALES, AND PATENT RIGHTS REGARDING THIS DEVICE OR DRAWING ARE RESERVED EXCEPT WHERE EXPLICIT RIGHT IS GRANTED IN WRITING.

Diversified Air Systems, Inc.
Phone: 800-264-8958

DRAWN BY: CB
DATE: 10-4-99
SCALE:

TITLE: **PORTABLE PAINT BOOTH**

DRAWING NO.: FB-800 (42-2340)