

SPECIFICATIONS:

CONSTRUCTION: 16 Ga. welded, zinc coated, steel cabinet, finished with a Powder-Coat finish. Includes removable panels for access to filters, lifting angles on top of unit, and a spark resistant, direct drive B.I. blower in an acoustic

lined blower compartment. Motor starters/ disconnects NOT included.

WEIGHT: 520 lbs.

AIRFLOW: 5000 CFM (STD AIR) 4500 CFM W/HEPA or V-Bank

NOISE: 77dBA

ELECTRICAL: \Box 3HP 208-230/460/3/60, 7.8-7.2/4 amps, std. \square 3HP 230/1/60, 11.7 amps, opt.

FIRE SUPPRESSION: Equipment provided by others.

PREFILTERS: \square (2) 24 x 72 x 2 Poly, opt.

☐ (36) 24 x 24 x 2 MERV 11, opt.

□(12) 2" MERV 11 and (12) 4" 30% pleat, opt.


□(12) 2" MERV 11 and (12) 4" MERV 14, washable synthetic, opt.

AD OPTION: □(12) 2" MERV 11 and (12) 3" 30 lb. AD modules, refillable

> □(12) 2" MERV 11 and (12) 2" charcoal/poly pads (replaceable) w/(12) 2" poly after-filters

OTHER OPTIONS: Pressure gauge kit indicates filter changes.

☐ Side shields



WG) ij PRESSURE STATIC

CUBIC FEET/MIN. (CFM)

THE DEVICE DEPICTED AND DESCRIBED HEREON EMBODIES PROPRIETARY INFORMATION OWNED BY AIRFLOW SYSTEMS, INC. ALL DESIGN, MANUFACTURING, REPRODUCTION, SALES, AND PATENT RIGHTS REGARDING THIS DEVICE OR DRAWING ARE RESERVED EXCEPT WHERE EXPLICIT RIGHT IS GRANTED IN WRITING.

Diversified Air Systems, Inc. Phone: 800-264-8958

DRAWN BY DATE 5-7-08 PANEL FILTER POWER BOOTH

DRAWING NO.: PFPBSPEC (79-4462/A)

